

Технический паспорт
Модуль кассетный 1x8 SC/APC, SIBVOLS B-130

Рабочие длины волн	1310-1550 нм	Температура хранения	от -40 до +85 °C
Тип волокна	G657A1	Длина волокна, м	25CM
Тип коннектора	SC/APC	Габаритные размеры	4x4x40 мм

Item	IL (dB)			PDL (dB)			RL (dB)		
Длина волны, нм	@1310	@1490	@1550	@1310	@1490	@1550	@1310	@1490	@1550
Спецификация	Макс. 9.8			Макс. 0.2			≥ 55		
Port 1	9.71	9.32	9.79	0.04	0.04	0.03	Pass	Pass	Pass
Port 2	9.41	9.45	9.33	0.03	0.03	0.03	Pass	Pass	Pass
Port 3	9.50	9.74	9.60	0.03	0.04	0.03	Pass	Pass	Pass
Port 4	9.31	9.53	9.78	0.03	0.04	0.03	Pass	Pass	Pass
Port 5	9.70	9.69	9.41	0.03	0.04	0.04	Pass	Pass	Pass
Port 6	9.51	9.41	9.52	0.04	0.03	0.03	Pass	Pass	Pass
Port 7	9.71	9.66	9.40	0.03	0.03	0.03	Pass	Pass	Pass
Port 8	9.80	9.57	9.34	0.03	0.03	0.03	Pass	Pass	Pass
Input	N/A						N/A		
Макс.	9.80	9.74	9.79	0.04	0.0	0.04	N/A		
Мин.	9.31	9.31	9.33	0.03	0.03	0.03	N/A		
Сред.	9.58	9.55	9.52	0.03	0.03	0.03	N/A		
Uniformity (≤ 0.8 dB)	0.49	0.44	0.46	Directivity (dB)			≥ 55		